

flashfs[0]: Bytes available: 60898994
flashfs[0]: flashfs fsck took 1 seconds.
...done Initializing Flash.

Boot Sector Filesystem (bs:) installed, fsid: 3
Parameter Block Filesystem (pb:) installed, fsid: 4

Loading "flash:/pt3000-i6q4l2-mz.121-22.EA4.bin"...

[OK]

Restricted Rights Legend

Use, duplication, or disclosure by the Government is
subject to restrictions as set forth in subparagraph
(c) of the Commercial Computer Software - Restricted
Rights clause at FAR sec. 52.227-19 and subparagraph
(c) (1) (ii) of the Rights in Technical Data and Computer
Software clause at DFARS sec. 252.227-7013.

cisco Systems, Inc.
170 West Tasman Drive
San Jose, California 95134-1706

Cisco Internetwork Operating System Software
IOS (tm) PT3000 Software (PT3000-I6Q4L2-M), Version 12.1(22)EA4, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2006 by cisco Systems, Inc.
Compiled Fri 12-May-06 17:19 by pt_team

Cisco WS-CSwitch-PT (RC32300) processor (revision C0) with 21039K bytes of
memory.

Processor board ID FHK0610Z0WC
Running Standard Image
6 FastEthernet/IEEE 802.3 interface(s)

63488K bytes of flash-simulated non-volatile configuration memory.

Base ethernet MAC Address: 00D0.5852.D622

Motherboard assembly number: 73-5781-09

Power supply part number: 34-0965-01

Motherboard serial number: FOC061004SZ

Power supply serial number: DAB0609127D

Model revision number: C0

Motherboard revision number: A0

Model number: WS-CSwitch-PT

System serial number: FHK0610Z0WC

Cisco Internetwork Operating System Software
IOS (tm) PT3000 Software (PT3000-I6Q4L2-M), Version 12.1(22)EA4, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2006 by cisco Systems, Inc.
Compiled Fri 12-May-06 17:19 by pt_team

Press RETURN to get started!

Switch>ena

Switch#?

Exec commands:

clear	Reset functions
clock	Manage the system clock
configure	Enter configuration mode
connect	Open a terminal connection
copy	Copy from one file to another
debug	Debugging functions (see also 'undebug')
delete	Delete a file
dir	List files on a filesystem
disable	Turn off privileged commands
disconnect	Disconnect an existing network connection
enable	Turn on privileged commands
erase	Erase a filesystem
exit	Exit from the EXEC
logout	Exit from the EXEC
more	Display the contents of a file
no	Disable debugging informations
ping	Send echo messages
reload	Halt and perform a cold restart
resume	Resume an active network connection
setup	Run the SETUP command facility
show	Show running system information

Switch#configure

Configuring from terminal, memory, or network [terminal]? terminal

Enter configuration commands, one per line. End with CNTL/Z.

Switch(config)#interface ?

% Unrecognized command

Switch(config)#interface inter

Switch(config)#interface inter

Switch#

%SYS-5-CONFIG_I: Configured from console by console

Switch#config terminal

Enter configuration commands, one per line. End with CNTL/Z.

Switch(config)#interface vla

Switch(config)#interface vlan

% Incomplete command.

Switch(config)#intarfac

Switch(config)#intarface vla

Switch(config)#interface vlan 1

Switch(config-if)#ip ?

address Set the IP address of an interface

helper-address Specify a destination address for UDP broadcasts

Switch(config-if)#ip address 192.168.1.2 255.255.255.0

Switch(config-if)#?

Interface configuration commands:

arp Set arp type (arpa, probe, snap) or timeout

```
description  Interface specific description
exit         Exit from interface configuration mode
ip           Interface Internet Protocol config commands
no           Negate a command or set its defaults
shutdown     Shutdown the selected interface
standby      HSRP interface configuration commands
```

```
Switch(config-if)#no sh
```

```
Switch(config-if)#
```

```
%LINK-5-CHANGED: Interface Vlan1, changed state to up
```

```
Switch#
```

```
%SYS-5-CONFIG_I: Configured from console by console
```

```
ena
```

```
Switch# end
```

```
Translating "end"...domain server (255.255.255.255)
```

```
% Unknown command or computer name, or unable to find computer address
```

```
Switch#
```

```
Switch#
```

```
Switch#
```

```
Switch#
```

```
Switch#exit
```

```
Switch con0 is now available
```

```
Press RETURN to get started.
```

```
%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up
```

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

%LINK-3-UPDOWN: Interface FastEthernet0/1, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to down

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

%LINK-3-UPDOWN: Interface FastEthernet0/1, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to down

%LINK-5-CHANGED: Interface FastEthernet1/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up
Enter configuration commands, one per line. End with CNTL/Z.

Switch(config)#

%LINK-3-UPDOWN: Interface FastEthernet1/1, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/1, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to down

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up